1P3FFCB-USB-SERIAL

MOLI Certified Accessories

3.3ft (1m) USB-A to Serial Adapter Cable

StarTech · MSRP: $ 45.09



Add RS-232 serial communication support to USB-A enabled Data Terminal Equipment (DTE) using this 3.3ft (1m) straight through USB to Serial Adapter Cable.

WARRANTY INFORMATION

Duration: 2 Years

GENERAL INFORMATION

FTDI FT232R Chipset; Max Baud Rate: 921.6Kbps; 128 Byte RX and 256 Byte TX FIFO; Odd/Even/Mark/Space/None Parity Modes; 7 or 8 Data Bits; 1 or 2 Stop bits.

Solid one-piece molded TPE housing and Level-4 ESD protection (15kV air/8kV contact) enhance reliability and longevity; Copper shielding minimizes EMI/RFI interference; Gold-plated connectors; Extended operating temperature of -40°C to 80°C.

© 2026 Perdix Software, Inc. • **MOLI**™, **The MOLI System**™, **Multi-Operation Lean Intelligence**™, the MOLI Seal, MOLI Avatar, and MOLI trade dress are trademarks of Perdix Software, Inc. • All other marks are property of their respective owners and are used for identification purposes only. • Actual results vary by facility size, product mix, and baseline conditions. Availability, features, specifications, and pricing subject to change. • sku-X-1P3FFCB-USB-SERIAL • rev 2026-11-20-perdix • 2026-11-20

Need help picking the right accessories? **We're here.**

PERDIXSW.COM

Perdix Software
info@perdixsw.com
(585) 471-6800