



LA6-POE Signal Tower (off-white, stationary)

PATLITE • MSRP: \$ 851.00



## LA6 Signal Tower: Stationary, Off-White

For use with the MOLI Smart Stacklight feature.

### GENERAL INFORMATION

5 multi-color LEDs capable of displaying 21 colors, 11 selectable buzzer patterns, animated sequences driven by **PATLITE®** an internal timer, and configurable flash rates.

IP54-rated housing, -10 to +50 °C operating range, and a 60 mm diameter body.

Ethernet connection with PoE (Power over Ethernet) support, enabling single cable installation.

A mirroring function can extend visual and audible status from a primary unit to up to eight remote replicas without additional software.

Poles, mounts, and brackets are available for many common applications.

© 2026 Perdix Software, Inc. • MOLI™, The MOLI System™, Multi-Operation Lean Intelligence™, the MOLI Seal, MOLI Avatar, and MOLI trade dress are trademarks of Perdix Software, Inc. • All other marks are property of their respective owners and are used for identification purposes only. • Actual results vary by facility size, product mix, and baseline conditions. Availability, features, specifications, and pricing subject to change. • sku-S-LA6-5DSNWB-POE • rev 2026-10-06-perdix • 2026-10-06

Ready? Questions? **We're here.**



PERDIXSW.COM

Perdix Software  
info@perdixsw.com  
(585) 471-6800