

LA6-5DTNWB-POE

MOLI Certified Devices

LA6-POE Signal Tower (off-white, direct mount)
PATLITE · MSRP: $ 761.00



LA6 Signal Tower: Direct Mount, Off-White

For use with the MOLI Smart Stacklight feature.

GENERAL INFORMATION

5 multi-color LEDs capable of displaying 21 colors, 11 selectable buzzer patterns, animated sequences driven by an internal timer, and configurable flash rates.

IP54-rated housing, –10 to +50 °C operating range, and a 60 mm diameter body.

Ethernet connection with PoE (Power over Ethernet) support, enabling single cable installation.

A mirroring function can extends visual and audible status from a primary unit to up to eight remote replicas without additional software.

Poles, mounts, and brackets are available for many common applications.

© 2026 Perdix Software, Inc. • **MOLI**™, **The MOLI System**™, **Multi-Operation Lean Intelligence**™, the MOLI Seal, MOLI Avatar, and MOLI trade dress are trademarks of Perdix Software, Inc. • All other marks are property of their respective owners and are used for identification purposes only. • Actual results vary by facility size, product mix, and baseline conditions. Availability, features, specifications, and pricing subject to change. • sku-S-LA6-5DTNWB-POE • rev 2026-11-20-perdix • 2026-11-20

Perdix Software
info@perdixsw.com
(585) 471-6800